

2019 PRODUCT CATALOG

A WORLDWIDE SUPPLIER OF QUALITY COMPONENTS FOR THE ELEVATOR INDUSTRY



NOW OPEN

SHOP SCS ELEVATOR PRODUCTS ONLINE WWW.SCSELEVATORPRODUCTS.COM

CUSTOMER SUPPORT

(800) 783-4633

WWW.SCSELEVATORPRODUCTS.COM

info@scselevatorproducts.com

OUR DOOR IS ALWAYS OPEN

Here at SCS we are wholeheartedly committed to delivering the highest quality products while offering world-class customer service. Our team takes pride in every facet of what we do. We invite you to get to know who we are. Our doors are always open.






WELCOME

For over four decades, SCS Elevator Products has incorporated innovations to set the standard of excellence in elevator components.

Throughout our 40 year history, SCS has built a reputation for designing and manufacturing the highest quality products for customers while maintaining an industry leading standard of customer service.

OUR MISSION is to continually build and maintain a team of honest, hard-working successful individuals who are committed to servicing our customers. We promise to produce the highest quality products through a certified Quality Management System. We are dedicated to continuous process improvements and to maintain our ISO 9001 certification. Our ethics stand on high integrity and solid core values in our day-to-day commitment to our customers and to our company.

WE PROVIDE A SAFE WORK ENVIRONMENT FOR OUR EMPLOYEES.



Proudly made in the USA, Shipped Worldwide

WHAT CAN SCS DO FOR YOUR COMPANY?



DIE CASTING

Our depth of experience in die casting allows us to excel at projects that require tight tolerances and unique finishes. We offer polishing, straight lining, painting, and plating.




METAL STAMPING

SCS provides precision metal stamping services. We provide metal stamping product design assistance and rapid turnaround on production tooling and prototyped parts.



PLASTIC INJECTION MOLDING

In our plastic injection molding department we have a wide range of press sizes that can accommodate a variety of parts. We offer in-mold decorating, and applied decorative finishes.



DESIGN AND TOOL BUILDING

Whether it's adapting an existing tool or designing a new tool from concept, we have the expertise to exceed our customer's expectations. Using three-dimensional modeling for tooling, we can accommodate complete detailed mold designs in-house from simple MUD sets to complex dedicated molds.

SCS Elevator Products Inc. is associated and certified with:















- INSERT MOLDING
- PAD PRINTING
- HOT STAMPING
- SONIC WELDING
- LASER MARKING
- PLASTIC PLATING
- MID-VOLUME MOLDING
- IN MOLD DECORATING

EXPANDED LINE
OF ELEVATOR
SIGNS NOW
AVAILABLE!
FREGREIGHTER



SHOP ONLINE AT www.scselevatorproducts.com

OR EMAIL US AT customerservice@scselevatorproducts.com



Mr. Robley G. Cook

A Brief History of SCS Elevator Products Inc.

Robley G. Cook, a visually impaired man, first recognized the need for directional Braille signage to assist those who are also visually impaired. Cook identified the elevator industry as the primary market for his products and approached elevator manufacturers in the USA, soliciting for their business to purchase metal stamped Braille.

In 1983, Mr. Cook became ill and passed away. This presentation of our products and services is dedicated to the memory of our founder, Robley G. Cook, whose respect for quality and devotion to the service of our customers provides daily inspiration for our evolution and achievements. His ideals are still at the heart of what our company is today.



THE LOGO

The SCS logo stands for innovation, precision, and direction. Its distinctive and highly visible form represents two arrows (one up & down) that communicates the company's core mission of helping the visually impaired and society move forward. The colors are chosen to represent innovation and sustainability as well as manufacturing in the USA.



TABLE OF CONTENTS

- **8** CAB BRAILLE CAST
- **10 CAB BRAILLE CAST/RESIN**
- II CAB BRAILLE EMBOSSED METAL
- 12 JAMB BRAILLE CAST
- 13 JAMB BRAILLE RESIN/EMBOSSED
- 14 PAVE SERIES BUTTONS
- **16 CONTACT BASES**
- 17 MOUNTING FLANGES & SHIMS
- **18 DESTINATION DISPATCH**
- 20 SIGNS
- **22** ADDITIONAL PRODUCTS
- **24** SAFETY BARRICADES
- 25 STANDARD COLORS
- **26 FINISH CODES**
- 27 APPLICATION TECHNIQUE AND CLEANING INSTRUCTIONS

OUR QUALITY POLICY

SCS is dedicated to providing quality products that meet our customers' requirements, together with on time shipments and at the highest level of service. We are committed to continually improving the effectiveness of our quality management system.

-The Management & Staff of SCS Elevator Products



DIE CAST METAL

ANSI COMPLIANT CC2 & CC2THIN

Part Size Thickness Corner Radius

 $1.248'' \times 1.248'' (\pm .010'')$ 0.085" (0.125" with FLP5) / 0.035" 0.125"

DIE CAST METAL

ANSI COMPLIANT

Part Size 1.500" x 1.500" (± .010") **Thickness** 0.062" **Corner Radius** 0.125"



DIE CAST METAL

ANSI COMPLIANT CC5

Part Size Thickness 0.085"

1.375" (± .010")



DIE CAST METAL

CC6 ANSI COMPLIANT

Part Size

1.500" (± .010") Thickness 0.062"



DIE CAST METAL

CC7

Part Size Thickness Corner Radius Character Height

0.755" x 1.130" (± .010") 0.063"

0.125" 0.629"



DIE CAST METAL

CC10 & CC10THIN ANSI COMPLIANT

Part Size Thickness Corner Radius 0.175"

1.254" x 1.254" (± .010")

0.085" (0.125" with FLP5) / 0.035"

STANDARD SPECS (unless otherwise noted)

Finish Background Plated Character Height Standard Font Satin Nickel, Satin Bronze, Mirrored Stainless or Mirrored Bronze, White, Black, Nickel, Goldleaf or US26

Painted 0.625"

Helvetica Medium

Mounting Standard with Studs, Adhesive Available Upon Request or Back Flange Mounting



21

DIE CAST METAL

CC16 ANSI COMPLIANT

Part Size Thickness 0.085" 0.125"

DIE CAST METAL

CK1 ANSI COMPLIANT

Part Size 2.051" x 1.375" (± .010")
Thickness 0.0625"





DIE CAST METAL

CC14 ANSI COMPLIANT

Part Size 1.445" x 1.252" (± .010")
Thickness 0.063"

DIE CAST METAL

CC15 ANSI COMPLIANT

Part Size 1.250" (± .020")
Thickness 0.050"







DIE CAST METAL

LCC5H

Part Size Thickness 0.085"
Character Height Mounting (2) Cast Studs

DIE CAST METAL

CCPH1

Part Size 1.000" x 2.250" (± .020")
Thickness 0.125"
Corner Radius 0.063"
Character Height 1.500"
Painted

STANDARD SPECS (unless otherwise noted)

Designation Color
Background Color
Character Height
Standard Font

Mounting Standard with Studs, Adhesive Available Upon Request or Back Flange Mounting



DIE CAST METAL

CW1 (FITS DIE CAST CW2 BRAILLE)

Part Size Thickness Diameter Opening Mounting Finishes

2.750" x 1.500" (± .010") 0.125"

0.125" 1.528"

Surface or Flush (with flanges)

Satin Nickel, Satin Bronze, Mirrored Stainless or Mirrored Bronze. Painted: Black, Nickel or Goldleaf.





RESIN

2010056 FITS WITH CCU1 AND RCU1

Part Size Thickness Diameter Opening Mounting Finishes

3.480" x 1.700" 0.130"

1.366" (designed to fit 1.350" button body)
Studless (uses studs from braille & threaded body of bottom)
Satin Tri-Chrome - 2010056

Black - 2010057

Mirrored Chrome - 2010091 PVD Mirrored Bronze - 2010141



DIE CAST METAL

CW11190 (FITS DIE CAST CW2 BRAILLE)

Part Size Thickness Diameter Opening Mounting

2.906" x 1.66" 0.115" 1.190"

Studless (uses studs from braille & threaded body of button)



DIE CAST METAL

CW2 ANSI COMPLIANT

Part Size Thickness

1.560" x 1.358" (± .010")

ess 0.053"



DIE CAST METAL

CCU1 ANSI COMPLIANT

Part Size 1.955" Thickness 0.070"

1.955" x 1.358" (± .010")



RESIN

RCU1 ANSI COMPLIANT

Part Size Thickness Designation Color Background Color

1.955" x 1.358" (± .010") 0.070"

White Black

STANDARD SPECS (unless otherwise noted)

Designation Color Background Color Character Height Standard Font Satin Nickel, Satin Bronze, Mirrored Stainless or Mirrored Bronze. Painted: White, Black, Nickel, Goldleaf or US26.

Painted 0.625"

Helvetica Medium

Mounting

Standard with Studs, Adhesive Available Upon Request or Back Flange Mounting



MARK MUNSON

I really enjoy meeting new people and learning about their company. Working with new and existing customers on projects and helping to make their job easier is what I love.

VICE PRESIDENT OF SALES



EMBOSSED METAL

EC1 ANSI COMPLIANT

Part Size 1.250" x 1.250" (± .020")
Thickness 0.032"
Corner Radius 0.062"



EMBOSSED METAL

EK1

Part Size 2.051" x 1.375" (± .020")
Thickness 0.032"



EMBOSSED METAL

EC1125 ANSI COMPLIANT

Part Size Thickness 0.032" (± .020")
Corner Radius 0.125"



EMBOSSED METAL

EC1R

Part Size 1.375" (± .020")
Thickness 0.032"

STANDARD SPECS (unless otherwise noted)

Designation Color
Background Color
Character Height
Standard Font

Mounting Standard with Adhesive or (1) Stud



JENNIFER MATZEK

Teaming up with our customers to assure they receive the parts they require and have the best customer service experience possible.

SALES TEAM MEMBER/DATA ENTRY





DIE CAST METAL

CJT24 ANSI COMPLIANT

DIE CAST METAL

CJ3

Part Size 3.00" x 4.00" (± .010")
Thickness 0.090"
Corner Radius 0.031"





DIE CAST METAL

LCJ229

 Part Size
 2.500"

 Thickness
 0.080"

 Character Height
 0.400"

 Corner Radius
 0.125"

2.500" x 4.000" (± .010") 0.080" 0.400" Title / 3.000" Designation RESIN RJ4

Part Size
Thickness
Corner Radius
Designation Color
Background Color
Mounting

4.000" x 4.000" (± .010")
0.080
0.0625"
White
Black
Adhesive

STANDARD SPECS (unless otherwise noted)

Designation Color Background Color Standard Font

Satin Nickel, Satin Bronze, Mirrored Stainless or Mirrored Bronze. Painted: White, Black, Nickel or Goldleaf.

Painted

Helvetica Medium

Mounting | Standard with Studs, Adhesive Available Upon Request or Back Flange Mounting



EMBOSSED METAL

ANSI COMPLIANT

Part Size 3.000" x 3.500" (± .020") Thickness 0.034"

EMBOSSED METAL

EJ34

Part Size 3.000" x 4.000" (± .020") **Thickness** 0.034"





EMBOSSED METAL

EJ325 & EJ4 ANSI COMPLIANT

Part Size EJ325 - 3.250" x 3.250" (± .020")

EJ4 - 4.000" x 4.000"

Thickness 0.034" **EJ45**

EMBOSSED METAL

Part Size 5.000" x 4.000" (± .020") Thickness 0.034"

EMBOSSED METAL

EJ5

Part Size 2.750" x 3.750" (± .020")

Thickness 0.034"



DIE CAST METAL

CJ5 CAST FRAME FITS WITH EJ5

Part Size 3.000" x 4.000" (± .010") **Thickness** 0.125"

Corner Radius 0.14"

Background Color Satin Nickel, Satin Bronze, Mirrored Stainless or

Mirrored Bronze. Painted: White, Black, Nickel or

Goldleaf.

Adhesive or (2) Cast Studs Mounting



STANDARD SPECS (unless otherwise noted)

Designation Color Satin Stainless, Satin Bronze, Mirrored Stainless or Mirrored Bronze. Painted: White, Black, Nickel or Goldleaf.

Background Color Natural or Painted 0.0625" **Corner Radius** 2.000" **Character Height**

Standard Font Helvetica Medium

> Standard with Adhesive, (4) 0.125" Corner Holes with Screws or (2) or (4) 6/32 x .375" Weld Studs Mounting

The PAVE Series

Protection Against Vandalizing Elevators

Discover our newly redesigned vandal prevention buttons. With 2 body styles and sizes, 3 finish options and 12 target styles available to choose from, our latest PAVE Button is the most versatile that we have ever offered.

Design your own button using numerous combinations available

Р	3	5	0		Р	F	I	L		S	S
{ PAVE	PAVE Series Button Body } { PAVE Series Target Style			} {	Finish	Code					



FINISH CODE FINISH CODE DESCRIPTION

Stainless Steel

SB Satin Bronze (PVD Coated)

BK Black (PVD Coated)

Projecting

PAVE Series Target Style

Illuminating Indicator Concave Flat Concave Flat Flat Concave **PFIL** PC00 **PFOO PFIO PCIO PCIR** CA COMPLIANT SS SB

Protect your Elevator HE LATEST IN VANDAL PRE



PAVE Series Button Body Styles and Sizes

		• •	
1.35"	1.35"	1.26"	1.26"
No Halo	Halo	No Halo	Halo
P350	P35H	P260	P26H
SS			
SB			

r.		Flush					
Rings				Ring	JS		
			Indic				
Flat	Flat	Domed	Domed	Domed	Domed		
PFIR	PFRO	FD00	FDIO	FDIR	FDRO		
			0				

MULTI-VOLT (3LED) 24 to 120 VOLT





2010018 - CB3B **Blue LED**



2010014 - CB3R **Red LED**



2010020 - CB3G **Green LED**



2010012 - CB3W White LED



2010016 - CB3A Amber LED

CONTACT BASES

MULTI-VOLT (1LED) 6 to 120 VOLT





2009262 - CB1B Blue LED



2009259 - CB1W **White LED**



2009260 - CB1R **Red LED**



200926T - CB1A Amber LED



2009263 - CB1G **Green LED**



2009258 - CB0 **No LED**

CONTACT BASES


LOW-VOLT (1LED) 2 VOLT






2012026 - CB1R-LV **Red LED**

NOTE: Old part numbers have been crossed out with a RED line.




FOR USE WITH: CC2, CC3 ,CC5 ,CC6

FLM₁



FOR USE WITH: CST1, CJ6

FLM4



FOR USE WITH: CC5

FLP₁




SUE HUFFMAN

I enjoy the personal relationships I develop


with our customers when helping them decide the parts they need for their projects. Knowing they are very satisfied and grateful for my help makes my day!

SALES TEAM MEMBER/CUSTOMER CARE




FOR USE WITH: CC2, CC3 ,CC5 ,CC6

FLM₂




FOR USE WITH: CJT24

FLM5



FOR USE WITH: CC2

FLP5



FOR USE WITH: CC2, CC3, CC5, CC6, CC7

SHIR SHIM



DIANA HANSEN

Feeling accomplished when expediting orders to meet a customer's dock date and/or helping customers determine the parts needed.

RFQ COORDINATOR/CUSTOMER CARE





DIE CAST METAL

CJ61116B114 CA STAR

Part Size Thickness Corner Radius Mounting 3.525" x 3.525" (± .010") 0.090"

0.031"


Standard with Studs, Adhesive Available Upon Request or Back Flange Mounting DIE CAST METAL

CJ6

Part Size Thickness Corner Radius Mounting 3.525" x 3.525" (± .010")

0.090" 0.031"

Standard with Studs, Adhesive Available Upon Request or Back Flange Mounting



Many options available!

Please call to request a drawing.



Floor -- Marking

- Elevator ID

EMBOSSED METAL

EJ229 ANSI COMPLIANT

Part Size
Thickness
Corner Radius
Designation Color
Background Color
Mounting

4.000" x 7.000" (± .010")

0.034" 0.0625"

White, Satin Stainless, Satin Bronze Black, Satin Stainless, Satin Bronze

Standard with Adhesive, (4) 0.125" Corner Holes

or (2) Vertical Studs

STAINLESS STEEL

DD229 ANSI COMPLIANT

Part Size Thickness Corner Radius Character Material Designation Color Background Color 4.000" x 7.000" (± .010")

18 ga. Square

erial Applied Raised Acrylic

Black

Color Satin Stainless

Mounting Standard with Adhesive or (4) Corner Studs

STANDARD SPECS (unless otherwise noted)

Designation Color Character Height Standard Font

Satin Nickel, Satin Bronze, Mirrored Stainless or Mirrored Bronze. Painted: White, Black, Nickel or Goldleaf.

2.000"

Helvetica Medium

Floor Marking

Elevator ID



DIE CAST METAL

ANSI COMPLIANT CJ7

Part Size 3.525" x 3.597" (± .010") **Thickness** 0.090"




Mounted together, the CJ7 & CJ8 give the appearance of one large die cast plate. Stud locations are available upon request.

DIE CAST METAL

CJ8 ANSI COMPLIANT

Part Size 3.525" x 3.597" (± .010") Thickness 0.090"





DIE CAST / RESIN

CR229A ANSI COMPLIANT

Part Size 5.190" x 9.780" (± .010")

Background Color Black Resin Frame with 2 - CJG and 1 - CS6

Adhesive

Thickness 0.230"

Mounting

STANDARD SPECS (unless otherwise noted)

Satin Nickel, Satin Bronze, Mirrored Stainless or Mirrored Bronze. Painted: White, Black, Nickel or Goldleaf. **Designation Color Background Color** Painted

Corner Radius Sauare 2.000" **Character Height**

Standard Font

Mounting Standard with Studs, Adhesive Available Upon Request or Back Flange Mounting

EXPAND NOW AVA

SHOP ONLINE AT www.scselevatorproducts.com

OR EMAIL US AT customerservice@scselevatorproducts.com





METAL / LEXAN

SVB80

Part Size Symbol Height Symbol Color Background Color 4.000" x 4.000" (± .010") 3.130"

Blue

White Matte Plastic, Satin Stainless, Satin Bronze, Mirrored Stainless or Mirrored Bronze

FIREFIGHTERS' OPERATION

Insert fire key and turn to "ON' Press desired floor button Press "CALL CANCEL" button

Press and hold "DOOR CLOSE" button Press and hold "DOOR OPEN" button With doors open, turn key to "HOLD'

With doors open, turn key to "OFF"

Also Available:

SVB41 - PHASE II ANSI 1996 SVB59 - PHASE II ANSI 1998 SVB79 - PHASE II ANSI 2000

METAL / LEXAN

SVB12 PHASE II ANSI 1993

Part Size Character Height Text Color Background Color 6.900" x 4.400" (± .010") 0.250" Title / 0.188" Text

Black or White

White or Black Matte Plastic, Satin Stainless, Satin Bronze, Mirrored Stainless or Mirrored Bronze

FIREFIGHTERS' OPERATION TO RECALL ELEVATORS

INSERT FIRE KEY AND TURN TO "ON"

FIREFIGHTERS' **OPERATION**

TO RECALL ELEVATORS INSERT FIRE KEY AND TURN TO "ON" NORMAL OPERATION KEY "BYPASS" THEN KEY "OFF"

FIREFIGHTERS' **OPERATION**

TO RECALL ELEVATORS INSERT FIRE KEY AND TURN TO "ON" NORMAL OPERATION KEY "RESET" THEN KEY "OFF"

SVB70R - Not available in Black Matte Plastic

METAL / LEXAN

SVB6 PHASE I ANSI COMPLIANT

Part Size Character Height Text Color Background Color

4.000" x 1.450" (± .010")

0.250" Black

White Matte Plastic, Satin Stainless, Satin Bronze, Mirrored Stainless or Mirrored Bronze

METAL / LEXAN

SVB70 & SVB70R PHASE I ANSI COMPLIANT

Part Size Character Height Text Color Background Color

3.375" x 3.000" (± .015) 0.250" Title / 0.188" Text

White or Black

Black Matte Plastic, Satin Stainless, Satin Bronze, Mirrored Stainless or Mirrored Bronze



Also available in:

Codes

FL: SVB104 MD: SVB31 HOUSTON: SVB123



2011060 ICOF Braille Plate 5.000" x 2.000" (± .020")



METAL / LEXAN

SVB13 ANSI COMPLIANT APPENDIX H, APPENDIX O

Part Size Character Height Flame / Picto Color **Background Color** 5.000" x 8.000" (± .020") 0.300" Text / 6.000" Flame Graphic Black Text and Pictograms, Red Flame White Matte Plastic, Satin Stainless, Satin Bronze, Mirrored Stainless or Mirrored Bronze

METAL / LEXAN

SVB30 CA CODE

Part Size Character Height Flame / Picto Color **Background Color**

5.000" x 8.000" (± .020") 0.300" Text / 4.000" Flame Graphic Black Text and Pictograms, Red Flame White Matte Plastic, Satin Stainless, Satin Bronze, Mirrored Stainless or Mirrored Bronze

STANDARD SPECS (unless otherwise noted)

Material Thickness Corner Radius Standard Font Mounting

0.032" - Metal / 0.020" - Lexan Sauare Helvetica Medium Adhesive

*Metal plate is for display view only









(INSERT ONLY)

R380, R580 & R580TRIM

Part Size R380 - 3.130" x 4.110"

R580 - 4.221" x 5.938"

R580TRIM - 4.310" x 6.830"

Flame/Picto Color Red Flame, Black Pictograms with White,

Satin Stainless or Satin Bronze Background

Back Flange Flush Mount Mounting

Cutout 2D Part Outline File Provided upon request,

When requesting indicate preferred file format.



CAST / RESIN

CST1 / RST1 ANSI COMPLIANT

Part Size

CST1 (Cast) - 3.490" x 3.490" (± .010") RST1 (Resin) - 3.510" x 3.510" (± .010")

Corner Radius Part Thickness Symbol Color Background Color

0.125" Blue

0.125"

CST1 - Satin Stainless, Satin Bronze, Mirrored Stainless, Mirrored Bronze. Painted: White, Nickel or Goldleaf

RST1 - White or Satin Silver

Mounting

CST1 - Standard with Studs, Adhesive Available **Upon Request or Back Flange Mounting**

RST1 - Adhesive Only



CAPACITY 2000 LBS.

3.250" x 1.250" (± .020")



ALUMINUM

ALUMINUM

SUBCAP CAPACITY PLATE

Part Size

Thickness

Character Height

PHASE I ANSI COMPLIANT SUB229COP

0.375"

0.020" Aluminum

Part Size 3.250" x 1.250" (± .020") **Character Height** 0.500"

> Thickness 0.020" Aluminum

ALUMINUM

ANSI COMPLIANT APPENDIX H, APPENDIX O **SUB229**

Part Size Character Height Thickness

4.000" x 4.000" (± .010") 0.625" Title / 3.000" Designation 0.020" Aluminum

STANDARD SPECS (unless otherwise noted)

Thickness **Text Color Background Color** 0.020"

White, Black, Satin Silver or Satin Gold Black, Satin Silver or Satin Gold

Standard Font Mounting

Helvetica Medium Adhesive



DIE CAST METAL

ANSI COMPLIANT CC22.425

Part Size Thickness Corner Radius Character Height Designation Color Background Color Mounting

2.425" x 1.250" (± .010") 0.085"

0.125" 0.625"

*See Cast Finishes below

Painted

Standard with Studs or Adhesive Available Upon Request

Background Color



DIE CAST METAL

ANSI COMPLIANT CIP₁

Part Size Thickness Corner Radius Symbol Height Symbol Color

1.575" x 1.063" (± .010") 0.052"

0.059" 0.500"

*See Cast Finishes below **Painted**

Mounting

Adhesive Only



CAPACITY 2100 LBS.

DIE CAST METAL

CM1

Part Size Overall Part Thickness Symbol Color Background Finish Mounting $2.495'' (\pm .010'')$ diameter opening

0.187"

Painted Red and Black *See Cast Finishes below

2.990" sq. Back Flange Flush Mount, 4 x 0.200" Mounting Holes

CP1

Thickness Capacity Height Duty Load Height/Color Background Color Mounting

Part Size

DIE CAST METAL

3.375" x 1.125" (± .010")

0.125" 0.250" Raised

> 0.240" / Black Laser Etched *See Cast Finishes below

> > 2011009

Standard with Studs or Adhesive Available Upon Request

2011010

Over 400 layouts offered! Please call to request drawing.



2010108









2010110

2010111

KEY SWITCH COLLARS

Part Size

1.340" round

Please request drawing

Flats Text Color Mounting .635 or .692 White

Surface Mount

KEY SWITCH **COLLAR HALO**

Part Size

1.700" round 0.D.

Mating Parts

Please request drawing 2010108, 2010109, 2010110, 2010111

STANDARD SPECS (unless otherwise noted)

Cast Finishes Standard Font Helvetica Medium

Satin Nickel, Satin Bronze, Mirrored Stainless or Mirrored Bronze, Painted: White, Black, Nickel or Goldleaf,



BRIAN HILFRANK

Identifying a customer's pain, then collaboratively figuring out a way to match the companies capabilities in order to eliminate that pain, is what I find the most gratifying.

REGIONAL SALES MANAGER









Please Call SCS for Braille Tags

DIE CAST METAL

CFHR

Part Size Part Thickness Symbol Color

3.078" round (± .010")

0.125"

Satin Nickel, Satin Bronze, Mirrored Stainless or Mirrored Bronze. Painted: White, Black, Nickel or Goldleaf.

Background Color Mounting

Painted

Standard with Studs, Adhesive Available Upon

Request

DIE CAST METAL

CI58HE

Character Height

0.625"

Finish

Satin Stainless, Satin Bronze, Mirrored Stainless or Mirrored Bronze. Painted: White, Black Nickel or Goldleaf.

Mounting

Standard with Studs





METAL

SVB136RSS

Part Size Fireman's Hat Color **Background Color**

3.500" x 3.500" Red - Silk Screened

Satin Stainless, Satin Bronze, Mirrored Stainless

or Mirrored Bronze

DIE CAST METAL

CSOL

Part Size Thickness Symbol Color Mounting

3.091" (± .010") 0.125"

Blue with White Snake

Standard with Studs, Adhesive Available Upon Request



RESIN BOARD

EARED BARRICADE - 2017115

Approx. Spread Size Panels Per Set 4

100" x 36" (Combine sets for a wider barricade)






RESIN BOARD

HINGED BARRICADE - 2017215

Approx. Spread Size Panels Per Set

110" x 36" 4 - Comes Assembled





CORRUGATED PLASTIC

SINGLE PANELS, EARED BARRICADE

Thickness Panel Size Text/Picto Color

Black

0.394" 29.5" x 42"

STANDARD SPECS (unless otherwise noted)

Thickness Text/Picto Color Background Color

0.236" Black and Red Safety Yellow

- Customized graphics also available
- Free standing and portable
- Easy to assemble and dismantle for use and storage
- Strong and resilient for interior or exterior use





STANDARD COLORS DISCLAIMER

We strive to make the colors shown as accurate as possible. However, the colors printed above may not be an accurate depiction of the actual color. These images should be used as a guide only. If you would like a sample of any item, please contact us at 800-783-4633 or email us at info@scselevatorproducts.com.

METAL EMBOSSED / SIGNS

OPTION CODES	CHARACTER FINISH	BACKGROUND FINISH
BSS	Black	Satin Stainless
SSB	Satin Stainless	Black
BMS	Black	Mirrored Stainless
MSB	Mirrored Stainless	Black
BSB	Black	Satin Bronze
SBB	Satin Bronze	Black
ВМВ	Black	Mirrored Bronze
MBB	Mirrored Bronze	Black
WB	White	Black

DIE CAST

OPTION CODES	CHARACTER FINISH	BACKGROUND FINISH
SNB	Satin Nickel	Black
SBB	Satin Bronze	Black
WB	White	Black
US26B	US26	Black
MSB	Mirrored Stainless	Black
MBB	Mirrored Bronze	Black
NICB	Nickle Painted	Black
BNIC	Black	Nickle Painted
GLB	Goldleaf Painted	Black
BGL	Black	Goldleaf Painted



JAMIE KELLS

I love building relationships with my customers, taking time to fully understand what my customers are looking for and finding a solution to help them. SCS Elevator Products has so many unique products to offer, let me show you how we can be your solution.

SALES AND MARKETING

APPLICATION TECHNIQUE FOR ADHESIVE MOUNTED PARTS

To obtain optimum adhesion, the bonding surfaces must be clean and dry. We recommend you use a cleaning solvent mixture of isopropyl alcohol (rubbing alcohol) and water mixture (50/50 mix). Use proper safety precautions for handling solvent.

It may be necessary to seal or prime some surfaces prior to bonding. For instance, most porous fibered material (e.g wood) will require sealing to provide a unified surface. Firm pressure around perimeter of plate, when applying, develops better adhesive contact and thus improves bond strength.

The ideal application temperature range is 70° to 100° F (21° to 38° C). Application to surface at temperatures below 50° F (10° C) is not recommended because the adhesive becomes too firm to adhere readily. In some cases bond strength can be increased and ultimate bond strength can be achieved more quickly by exposure of the bond to elevated temperatures (e.g 150° F (66° C) for 1 hour). This provides better adhesive onto the surfaces.

Plates may appear to have slight bend. With proper application using the above directions, adhesive should overcome any such bend. If you have any questions regarding these instructions, please contact our office anytime.



A of a part of the second seco

CLEANING INSTRUCTIONS

Cleaning can be accomplished by wiping with a damp cloth and wiping dry. Make sure that a very soft cloth such a flannel or equivalent is used and that all wiping is done in the direction of the grain. Make sure that only light pressure is applied when wiping the material. Abrasive cleaners or materials should never be used.



310 Cannon River Avenue North Red Wing, Minnesota 55066

info@scselevatorproducts.com

A MORIDIM DE SUPRIER OF QUALITY COMPONENTS FOR THE ELEVATOR INDUSTRY